

1067

VELUX

HEALTH & SAFETY DATA SHEET

Composition/ Raw material

Sash /Frame:

Pinewood (Pinus Sylvestris) or polyurethane (solid or with plywood Core).

Double sealed unit:

Standard or special style glass of normal composition.

Coverings:

Coated aluminium, copper or zinc.

Environment Statement

This product has neither been treated with nor contains any materials constituting a health hazards under normal use.

Packaging

When removing product from protective carton, care must be taken by first party to ensure, that no injuries occur from raw cardboard edges or sharp staples

Third parties must be made aware of the possibility of staples springing out when the carton is opened.

Protective gloves/glasses should be worn.

Storage and stacking

The product must be stored in dry, cool conditions.

The window can be stacked vertically **on pallets** to a maximum height of 8m. This does not apply to the window types GVA, GVO and GVT, which can only stacked horizontally.

All windows can be stacked in horizontal position, up to 2 x 6 Windows (height 2.5m).

Handling (in & out of carton)

When handling the product in the carton – **do not slide through hands** – Use lifting handholds provided in carton.

When handling the products out the carton – **do not slide through hands** – Splinters/ Chipped off wood as well as sharp aluminium corners may be present.

Protective gloves should be worn.

Kinetic handling methods should be used.

Installation

Before attempting installation, all enclosed instructions should be read and fully understood.

Always be aware of the "dead" weight of the product during installation.

Use fittings and screws provided during installation.

Protective gloves should be worn.

Replacement of pane

In case a defective pane is to be replaced, VELUX instructions must be followed.

User or homeowner

Before starting to use the new VELUX window, it is important that the **"User or Homeowner Information"** provided with the window is read carefully and understood.

The information contains directions for use, i.e.

- the opening and closing function
- the ventilation position
- cleaning of the window pane

and directions for maintenance of the window:

- wood or polyurethane
- lubrication of fittings
- cleaning of flashings
- minimising condensation

Further information

If further information is required, please do not hesitate to contact us at any of the VELUX Company Ltd sales offices listed below, or our technical department at Glenrothes.