

TECHNICAL DATA SHEET

JOY ELECTRIC SHOWERS

Joy 8.5kW / 9.5kW

Product Specification

| | |
|----------------------------|--------------------------------------|
| Product Code: | JOYT85 W / JOYT95 W |
| Finish: | White |
| Product Type: | Contemporary |
| Construction: | Plastic (ABS) |
| Supply: | Suitable for mains cold feed only |
| Inlet Connections: | 15mm push fit, 5 directional options |
| Outlet Connections: | G ½" |
| Working Pressures: | Min 0.7bar, Max 10.0bar |



Additional Information

- Instantaneous electric shower drawing water direct from the mains supply; ideal for installations without stored hot water and second bathrooms.
- Consistent showering temperature is provided. The temperature stabilising device compensated for changes in the water pressure caused by other household fittings.
- Safety devices include thermal cut out & pressure relief.
- 3 Power settings. [Cold, Warm/Eco, Hot] and a separate temperature control.
- On/Off is operated by Push Button, ensuring temperature setting remains unaffected after each use.
- Safety warning letters in a display panel indicate low pressure and therefore the shower should be turned off until pressure resumes.
- The phased shut down feature ensures all hot water is flushed out of the shower after use prolonging the shower life. This ensures lime scale build up is kept to a minimum.
- Push fit swivel inlet elbow pipe connection, enabling plumbing from 5 different directions.
- This shower is supplied with an adjustable riser kit and 3 mode rub-clean handset. The riser has a built in soap tray & integral hose retainer.
- Adjustable riser comes complete with adjustable top/bottom brackets so ideal to cover existing riser holes and tile joints.
- Incorporates a temperature control device (TCD) that activates when the temperature is too high & the water inside the heater gets too hot. The TCD will switch off the power to the heating elements and once the unit cools down to a safe temperature, will come on again.
- ThermoSafe™ Technology: Regulates the output water to minimise high/dangerous output temperatures for a safer showering experience.

TECHNICAL DATA SHEET

BRISTAN

Technical Advice: For further information please call 0844 7016273 or email customercare@bristan.com

Guarantee: 2 years covering manufacturing faults.

Compliance / Approvals

WRAS: Manufactured to comply with WRAS

BEAB safety: IWH 0757

BEAB EMC: IWH 0761

CE Mark: 

Flow Rates (litres per minute)

| System Pressure | 8.5kW | 9.5kW |
|---------------------|-------|-------|
| Maximum Flow @ 40°C | 4.0 | 4.5 |

Dimensions (mm)

