

Hardie® Backer External

How can our Hardie® Backer be used externally

- Only our 12mm Hardie® Backer board can be used externally
- Can be used externally for render, brickslip, tiles, external grade direct paint finish
- The board has to be 150mm above ground level
- Tile application = Adhesive to be external grade frost resistant and applied as per the manufacturer's recommendations
- Fixings to be of an external grade suitable for cement boards
- For cutting and handling of Hardie® Backer please follow our standard guidance as seen in the Hardie® Backer install guide
- Must be secured to the substrate with screws
- 12mm Hardie® Backer can be installed either way round (rough or smooth face)
- Number of fixings required – Stud centre dependent but allow for a minimum of 20 per board @ 400mm stud.

Restrictions

- Vertical installation only and can't be used externally as a floor application
- Not suitable for being submerged in water or below ground level
- Do not leave exposed or unfinished – follow the James Hardie storage guidance in the Hardie® Backer install guide
- 6mm Hardie® Backer is not suitable for external use.
- Hardie® Backer is not suitable to be used as structural floor or deck board
- The board should not be dot and dab or adhesive fixed.

© 2024 James Hardie Europe GmbH. ™ and ® denote registered and unregistered trademarks of James Hardie Technology Limited and James Hardie Europe GmbH.

A2
fire-rated

15 Year
Warranty