


MATERIAL SAFETY DATA SHEET

EGGER(UK) Ltd

**EUROSPAN[®], EURODEKOR[®],
WEYROC & WEYROC PROTECT**



1. Product Information

Manufacturer/ Distributor	EGGER (UK) Limited
Address	Anick Grange Road, Hexham, Northumberland, NE46 4JS
Phone	01434 602191 Fax 01434 605103 Emergency 01434 602191
Tradename/Type	EUROSPAN [®] , EURODEKOR [®] , WEYROC, WEYROC PROTECT
Uses	Particleboard for use in furniture and construction industries.
Description	Straw to tan coloured wood particleboard (some grades may have green core or surface)

2. Information on ingredients

Wood: 82 - 84%; Solid Resin: 8 - 10%; Water: 7%; Solid Paraffin Wax: 0.5%; Total Extractable Formaldehyde (CASNo. 50-00-0): 0.008% max (Emission class 1); Silica: <0.05%; Green Dye (solids) 0 - 0.01% (moisture resistant grades)

3. Hazards identification

Harmful by inhalation (dust / formaldehyde). Effects of skin contact are not fully known and may vary.

4. First aid procedures

EYES: Irrigate with water. If discomfort persists obtain medical attention.
INHALATION: Remove from exposure. If discomfort persists seek medical attention.
SKIN: Wash off with soap and water.
INGESTION: Wash out mouth with water.

5. Fire fighting measures

Use: Water, CO₂. Dust from cutting and milling operations is an explosive hazard (see additional information). Thermal decomposition produces irritating and toxic gases including CO, aldehydes and organic acids.

6. Accidental release measures

Sweep or vacuum wood dust for recovery or disposal, avoid generation of dusty conditions. Provide good ventilation.

7. Handling and storage

Care should be taken during handling to protect hands from small splinters of wood. Follow good housekeeping practices; clean up areas where wood dust settles to avoid excessive accumulation of this combustible material. Avoid generation of explosive levels of wood dust in air. Store in a cool, dry, well ventilated area. Note: In poorly ventilated areas, particularly under moist and warm conditions, small traces of formaldehyde may be emitted.

8. Exposure controls

WEL Wood dusts : 8 hour WEL 5mg/m
WEL Formaldehyde - 8 hour WEL 2 ppm (2.5 mg/m³ STEL 15 minute 2 ppm (2.5 mg/m³)
Respirator: Approved respirator under dusty conditions recommended.
Ventilation: Local Exhaust: Due to explosive potential of wood dust when suspended in air, precautions should be taken to prevent sparks or other ignition sources in ventilation equipment. Use of totally enclosed motors is recommended.
Gloves: Recommended to reduce skin contact, except where moving machinery parts expose fingers to hazards.
Eyes: Safety glasses or goggles recommended.

9. Physical and chemical properties

Colour: Straw to tan (moisture resistant boards may have green surface or core). Density: 560 – 720 kg/m³

Ignition Temperature of Dust: 100°C

CREATING MORE FROM WOOD



10. Stability and reactivity

Thermal decomposition produces irritating and toxic gases including CO, aldehydes and organic acids. Avoid oxidising agents and drying oils. Keep away from sources of ignition.

11. Toxicological information

Quantitative data on the toxicity of this product are not available.
Chronic effects of skin contact with wood dust are not fully known and may vary.

12. Ecological information

Quantitative data on the ecological impact of this product are not available. Adverse effects on the environment cannot be excluded but unlikely when handled, stored, and disposed of appropriately.

13. Disposal considerations

The supplier can recycle the product. Recycling is the preferred route. If recycling is not possible the material should be sent for energy recovery. Landfill is not advised but can be used as a last resort. It is however the user's responsibility to ensure wastes are disposed of in accordance with all valid laws. European Waste Code: 170201/030105.

14. Transport information

No transport warning sign required.

15. Regulatory information

Within the UK, the use of this material must be assessed under the Control of Substances Hazardous to Health (COSHH) regulations.

16. Additional information / comments

Wood dust from cutting operations, is a strong to severe explosion hazard if dust "cloud" contacts an ignition source. Partially burned dust is especially hazardous if dispersed in air. 212°F (100°C) has been suggested as the upper temperature limit for continuous exposure of wood without risk of ignition. (Wood dust may require still a lower temperature. White pine flour as "cloud in air" requires 0.04 J minimum energy for ignition and can produce an explosion pressure of 113 psi maximum (0.8 MPa).

EUROSPAN® boards are classified as Class 3 Surface Spread of Flame (BS 476). EUROSPAN® boards are classified as Class 2 Surface Spread of Flame (BS 476).

For further information please view the Wood Panel Industry Federation (WPIF) web site www.wpif.org.uk for section 6 of the Panel Guide on Health & Safety.

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for consideration, investigation and verification. Buyer assumes all risk of use, storage and handling in compliance with applicable laws and regulations. EGGER (UK) Limited makes no warrant of any kind, express or implied, concerning the accuracy or completeness of the information and data herein. EGGER (UK) Limited will not be liable for claims relating to any parties use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are accurate, inaccurate, incomplete or otherwise misleading. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*First Issue (06/11/2001) Revised 13/12/05 updated section 8 in line with new workplace exposure limits.