



## **DECLARATION OF PERFORMANCE**

### **No SNF\_DOP\_015**

1. Unique identification code of the product-type:

**Dow Corning 796 PVC-U , Aluminium & Wood Silicone Sealant**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch number: see product packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Sealant for Facade: EN-15651-1: F-Ext-Int-CC**  
**Sealant for Glazing: EN-15651-2: G-CC**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Dow Corning Europe S.A.**  
**1 rue Jules Bordet, Parc Industriel zone C**  
**7180 Seneffe, Belgium**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not relevant**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3: System 3 for reaction to fire**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**EN 15651-1 & EN 15651-2 and reaction to fire system 3 and issued a test report**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Disclaimer** : The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, Dow Corning makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.



Not relevant

9. Declared performance

**Conditioning: Preparation B (According to ISO 8340)**

**Substrate: Glass (without primer)**

**Aluminum (without primer)**

Essential Characteristics	Declared performance	Harmonized standard
Reaction to fire	Class E	
Release of Chemicals	None	See product safety data sheet
Water Tightness & Air Tightness as determined by :		
Resistance to flow(ISO 7390)	≤3mm	EN 15651-1,2
Loss of volume (ISO 10563)	≤10%	EN 15651-1,2
Adhesion/Cohesion at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C) acc.to ISO 8339 modified	≤0.9MPa	EN 15651-1,2
Adhesion/Cohesion at maintained extension for non-structural sealants used in joints in cold climate areas (-30°C) acc.to ISO 8340 modified	No Failure	EN 15651-1,2
Adhesion/Cohesion properties after exposure to heat water and artificial light acc.to ISO 11431	No Failure	EN 15651-2
Elastic recovery (ISO 7389)	≥70%	EN 15651-2
Durability	Pass	EN 15651-1, 2

**Mortar M1 (with Primer P)**

**Mortar M2 (without primer)**

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

Not relevant

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Loriane Parisot  
High Performance Building AETS manager EMEA

Seneffe, 3<sup>rd</sup> February 2014

**Disclaimer** : The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, Dow Corning makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.



**Dow Corning**  
*Your partner in building the future*  
**CONSTRUCTION SOLUTIONS**



**Disclaimer** : The information contained in DoP and this presentation is provided in good faith and deemed accurate at the date of publication of this document. Notwithstanding any intended uses specified in this document, due to differing conditions of use, the user remains liable to ensure the Product is suitable for its intended uses and applications and is legally compliant for the same. Therefore, Dow Corning makes no warranty express or implied regarding the fitness of the Product for any particular purpose. This information should not be construed as legal advice. Sales of the Product remain subject to the applicable terms and conditions of sale. User should refer to the Product Safety Data Sheet any user guidance provided in connection with the use of the Product.