



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: [info@everbuild.co.uk](mailto:info@everbuild.co.uk)

website: [www.everbuild.co.uk](http://www.everbuild.co.uk)

## CONSTRUCTION PRODUCTS REGULATION

### DECLARATION OF PERFORMANCE

#### No JETCEM/1-CPR/2013

|  |   |
|--|---|
| 1. Identification Code                                     | <b>Jetcem Rapid Set Cement</b><br><br><b>Codes: JETCEM2, JETCEM3, JETCEM6</b>   |
| 2. Type, Batch and/or Serial Number                        | <b>For batch number see packaging</b>   |
| 3. Intended use  | <b>Concrete repair product for non- structural repair. CC Mortar (based on hydraulic cement)</b><br><br><b>EN1504-3 Principle 3.1</b>             |
| 4. Manufacturer  | <b>Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS90SW, UK.</b>                               |
| 5. Authorised Representative                               | <b>Not Applicable</b>   |
| 6. Assessment and Verification of Constancy of Performance | <b>System 2+</b>  |
| 7. Notified Body and Tasks                                 | <b>BSI (0086) Initial inspection and ongoing surveillance of F.P.C. system</b><br><br><b>Certificate of conformity reference 0086-CPD- 597711</b> |
| 8. European technical Assessment                           | <b>Not applicable</b>   |
|  |   |
|  |   |



**Building & DIY Products You Can Trust**

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

|   |  |
|---|--|
| 9. Declared Performance                   | <b>EN1504-3 (2005) ) Concrete repair product for non structural repair. CC mortar (based on hydraulic cement) Class R2</b> |
| Compressive Strength                      | <b>Class R4</b>  |
| Chloride ion content                      | <b>≤ 0.05%</b>   |
| Adhesion strength by pull off test        | <b>≥ 1.5MPa</b>  |
| Restrained shrinkage/expansion            | <b>NPD</b>   |
| Carbonation resistance                    | <b>NPD</b>   |
| Elastic Modulus                           | <b>≥ 15GPa</b>   |
| Thermal Compatibility: Part 4 Dry Cycling | <b>≥ 0.8MPa</b>  |
| Skid resistance                           | <b>NPD</b>   |
| Coefficient of thermal expansion          | <b>NPD</b>   |
| Capillary Adsorption                      | <b>≤0.5kg/m<sup>2</sup>h<sup>0.5</sup></b>   |
| Dangerous substances                      | <b>Complies with 5.4</b>   |
| Reaction to Fire                          | <b>Class A1</b>  |

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington - Technical Manager

Dated: Leeds, 1/7/201